

**Xerox**  
**DocuPrint N4525**  
**NETWORK LASER PRINTER**

For large workgroups with  
the most demanding  
performance requirements.



THE DOCUMENT COMPANY  
FUJI XEROX



# Xerox DocuPrint N4525

## NETWORK LASER PRINTER

<b>Created for Exceptional Performance</b>	<ul style="list-style-type: none"> <li>Fast print speed of 45 pages per minute. Optional duplex prints two-sided pages at 39 images per minute.</li> <li>Fastest first-print-out time in its class at only 4 seconds from ready mode.</li> <li>1200 dpi image quality at full rated speed.</li> </ul>
<b>Designed for Advanced Paper Handling</b>	<ul style="list-style-type: none"> <li>Up to 6 input sources for a total capacity of 3,550 sheets.</li> <li>Handles various paper stocks sizes from statement/A6 to ledger/A3. Paper weights from 64 to 200 gsm with variable fusing.</li> <li>Optional 3,000-sheet Finisher/Stacker provides job collation, stapling and hole punching.</li> </ul>
<b>Configured for Maximum Flexibility</b>	<ul style="list-style-type: none"> <li>Connectivity: 10/100Base - TX Ethernet, 10Base2 Ethernet, Token Ring, Parallel, Serial, USB.</li> <li>Printer Management: Local, via CentreWare or via Embedded Web Server using CentreWare Internet Services. Multi-vendor via PrinterMap. Via e-mail using MailLinX.</li> </ul>

### Specifications

<p><b>Print Speed</b> 45 pages per minute simplex, 39 images per minute duplex</p> <p><b>First Page Out</b> 4 seconds (ready mode); 7 seconds (standby mode)</p> <p><b>Processor/PDL</b> PowerPC 740 233 MHz G3 Class RISC processor, Adobe PostScript 3, PCL6 and PCL5e emulations</p> <p><b>Memory</b> 32 MB RAM, upgradable to 192 MB RAM</p> <p><b>Print Resolution</b> 1200 dpi image quality, 600 x 600 dpi, 300 x 300 dpi, Xerox Quad Dot halftoning, Xerox Image Enhancement</p> <p><b>Standard Network/Connectivity</b> 10/100BaseTX Ethernet, Bi-directional parallel, USB, (Token Ring, Serial, 10Base2)<sup>†</sup></p> <p><b>Automatic 2-sided Printing<sup>†</sup></b></p> <p><b>Paper Input Capability</b> 2 x 500-sheet trays; 50-sheet bypass feeder</p> <p><b>Paper Output Capability</b> 500 sheets face down; 3,000-sheet Finisher/Stacker with Stapler and Hole Puncher<sup>†</sup></p> <p><b>Monthly Duty Cycle</b> Up to 250,000 pages</p> <p><b>Network/Software Printer Management</b> Xerox CentreWare DP, CentreWare Internet Services, Xerox PrinterMap, CentreWare Sun OS/Solaris Services, Solaris Ready certified, Microsoft certified, PrintXchange supported, VIPP supported, SAP R/3, Tivoli OpenView, CA Unicenter, Microsoft Management Console (MMC), SNMP-standard MIBs and Xerox extended MIBs</p> <p><b>Font Capabilities</b> 35 Resident Adobe Type 1 fonts, 101 downloadable soft fonts, 45 PCL fonts, 10 Microsoft TrueType fonts, 35 Intellifonts, 1 PCL compatible bitmap font</p> <p><b>Printer Drivers</b> Windows 95/98/2000/Me and Windows NT 4.0, UNIX (Sun OS, Sun Solaris, HP/UX, IBM AIX, SGI, DEC), Macintosh, Linux RedHat</p> <p><b>Languages</b> Genuine Adobe® PostScript® 3™, PCL5e and PCL6 emulations with automatic sensing and switching</p>	<p><b>Paper Handling Media Types</b> 64 – 200 gsm bond and cardstock, coated or glossy papers, labels, envelopes, transparencies</p> <p><b>Media Sizes</b> Letter, executive, legal, statement, folio, ledger, post-card, A3, A4, A5, A6, B4, B5 Edge-to-edge printing on all paper sizes</p> <p><b>Finisher</b> (standard on FN model) 3,000-sheet Finisher/Stacker with Stapling and Hole-Punching: up to 50 sheets stapled per set, 3 staple positions, hole-punching capability included</p> <p><b>WorkSet Special Features Productivity Tools for the User</b> <i>Send Once, RIP Once, and Print Many</i> capability; Job pipelining to process multiple jobs concurrently; MailLinX – emails jobs to printer and sends alerts and status via email; Proof Print*; Secure Print*; Draft/toner saver modes; Separator sheets (for transparencies); Booklet printing; Auto tray select; Cover sheets; Print Anyway; Variable fusing; Edge-to-edge printing; Load While Run; Smart Jam Diagnostics; Fax-Friendly Black; N-Up</p> <p><b>Productivity Tools for the IT Manager</b> Web-based Printer Administration via Embedded Web Server, MailLinX e-mail alerts, PrinterMap, IPP support</p> <p><b>Operating Dimensions/Weight</b> 642 (W) x 486 (H) x 540 (D) mm 48.5 kg (110V), 52.6 kg (220V)</p> <p><b>Environmental</b> Temperature: 5° to 35°C Relative Humidity: 15% to 85% (noncondensing) Noise Level: 28 dB(A) standby, 55 dB(A) running</p> <p><b>Electrical</b> Two models: 110 – 127 VAC, 50/60 Hz; 220 – 240 VAC, 50/60 Hz, Sleep mode, Energy Star Compliant</p> <p><b>Regulatory</b> FCC Part 15, Subpart B, UL listed to UL 1950, Certified to CSA – C22.2 No.950, FDA 21 CFR Sub J, CE Mark applicable to directives 73/23/EEC and 89/336/EEC, TUV-GS Mark, IEC 950 Second Edition (EN 6095, EN 60825)</p> <p><sup>†</sup>Requires hard disk</p>
---	--

### Supplies

<b>Consumables</b>	
Toner Cartridge (30K yield at 5% coverage)	113R00195
Staple Cartridges (3 cartridges, 5,000 staples per cartridge)	108R00158
Maintenance Kit (300K yield) 220V contains: fuser cartridge, bias transfer roll, 15 feed rolls (3 for each paper input tray), gloves, cleaning cloth, instructions	109R00049
<b>Options<sup>†</sup></b>	
2,500 sheet Feeder	097S02560
100 Envelope Feeder	097S02567
Duplex Module	097S02561
200-sheet Face-up Bin	097S02564
3,000-sheet Finisher/Stacker with Stapler and Hole Puncher (4 hole position)	450S02181
Internal Hard Disk	097S02364
16-MB DIMM	097S02356
32-MB DIMM	097S02357
64-MB DIMM	097S02358
8-MB Flash DIMM	097S02360
Token Ring Interface Card	097S02363
Ethernet 10Base2 Interface Card	097S02362
RS232-C Serial Interface Card	097S02361



For information, please contact :



Official Printer