

THE DOCUMENT COMPANY
FUJI XEROX



Phaser 3310
Laser Printer



Perfect for the **small workgroup**

Fast. Versatile. And priced just right.



The Xerox Phaser 3310 laser printer is engineered to deliver a fast 14ppm output, with superb 1200dpi resolution for crisp, clear prints. And with a host of intelligent features for easy connectivity and cost savings, it is the laser printer of choice for today's office workgroups.

High Performance

- Prints at 14ppm with powerful 66MHz RISC Processor, for increased productivity
- Produces outstanding 1200dpi x 1200dpi resolution printouts outstanding image quality

Versatile Paper Handling

- Handle various types of media & paper sizes
- High input paper capacity of 1,200 sheets

Cost Saving Features

- Innovative Toner Save feature helps to reduce running costs
- N-up printing feature permits multiple page printing on a single sheet

Superior Network Connectivity

- Supports multiple network printing environments

Xerox printers. Xpect more.

Specifications

Print Speed (A4/letter)	14ppm/15ppm
First Page Out Time	< 15 sec
Warm Up Time	< 40 sec
Processor	66MHz RISC Processor
PDL	PCL6 emulation, PostScript 3 emulation*
Memory (Std/Max)	4MB/68MB
Print Resolution (Std/Max)	600 x 600dpi 1200 x 1200dpi (memory expansion recommended)
Standard Network/Connectivity	Bi-directional parallel (IEEE1284), USB, Ethernet 10/100 BaseTX†
Paper Input Capacity	Up to 1,200 sheets
Paper Output Capacity	250 sheets face down/100 sheets face up
Monthly Duty Cycle	12,000 pages
Paper Handling	
Paper Size	A4, Letter, Legal, Executive, B5, A5, Folio, 7¾ (Monarch), com 10, DL, C5, C6, B5
Paper Type	Plain paper, envelopes, labels, transparencies, card stock
Paper Feeder	550-sheet Paper Feeder, 100-sheet Multi-Purpose Tray
Network/Software	
Network Protocol	TCP/IP, IPX/SPX, DLC/LLC, Ethertalk, SNMP
Font Capabilities	45 Scalable, 1 Bitmap, 136 PS3 fonts with PS3 option
Printer Driver	Windows 95/98/2000/ME/NT/XP, Linux (Redhat 6.0), Macintosh (Mac OS 8.6)

Operating	
Dimensions/Weight	361(W) x 409(D) x 294.5(H)mm / 12.4 kg
Environment	Temperature 10 – 32°C Humidity 20 – 80% RH
Electrical	200 – 240 VAC, 60 Hz/100 – 127 VAC, 50 Hz
Power Consumption	Power save mode: < 12W Printing: 350W
Acoustic Noise	Standby: < 35dB, Operating < 48dB
Consumables	
	Print Cartridge (3,000 yield at 5% coverage)
	Print Cartridge (6,000 yield at 5% coverage)
*Options	
	550-sheet Paper Feeder
	PostScript 3 Kit
	8MB Memory
	16MB Memory
	32MB Memory
	Network Interface Card (10/100 BaseTX)



For more information, please contact



Xerox, The Document Company, the stylised X and Phaser are registered trademarks/trademarks. All other names mentioned in this brochure are trademarks of their respective companies. Whilst this information is correct at the time of printing, Fuji Xerox Asia Pacific Pte Ltd reserves the right to change the specifications of the equipment described herein without notice.