

Xerox
Phaser 5400
Laser Printer

A new dimension of superiority
in speed and performance



THE DOCUMENT COMPANY

FUJI XEROX



Xerox Phaser 5400 Laser Printer



Best-in-class Performance

- True 1200 x 1200dpi resolution for the sharpest text, graphics, photos, and charts
- Fast 40 pages-per-minute printing; duplex option prints two-sided pages at 29 impressions-per-minute
- A powerful G3 Class 266MHz PowerPC controller
- Incredible first-print-out time of only 9 seconds

Unbeatable Value

- Provides a wide variety of media handling options
- High Capacity Printer Cartridge with a yield of 20,000 impressions (5% coverage) and duty cycle of up to 200,000 pages-per-month maximise printer uptime

Superior Versatility

- Handles different kinds of paper sizes and types
- 10/100Base-TX Ethernet, Parallel, and USB standard on all models
- Adobe PostScript 3, PCL 6, PCL5e emulations standard on all models
- Industry-leading printer management tools with CentreWare Web Printer Administration and CentreWare IS Embedded Web Server

Specifications

Print Speed	40 pages per minute (ppm)
First Page Out	9 seconds
Processor/PDL	266MHz PowerPC processor, Adobe PostScript 3, PCL6 and PCL5e emulations
Memory (Standard/Maximum)	32MB / 192MB RAM
Print Resolution	True 1200 x 1200dpi, 1200dpi Image Quality, 600 x 600dpi
Standard Network/Connectivity	10/100Base-TX Ethernet, Bi-directional parallel, USB
Automatic 2-Sided Printing	Optional
Paper Input Capability	500 sheet tray, 150 sheet bypass feeder
Paper Output Capability	500 sheet face down tray
Monthly Duty Cycle	Up to 200,000 pages/month

Network/Software

Printer Management: CentreWare Web (Win 2K, NT), CentreWare IS Embedded Web Server, CentreWare Printer Management Suite (DP, MMC, UNIX/Linux, HP OpenView, Tivoli NetView, CA Unicenter) PrinterMap, Xerox NDP5 Gateway, SAP R/3, VIPP certified, SNMP MIB

Font Capabilities: 39 resident PostScript fonts, 1 PCL bitmap typeface, 80 PCL resident scalable typefaces

Printer Drivers: Windows 95/98/Me, Windows 2000, Windows XP, Windows NT 4.0, UNIX (HP-UX, Solaris, IBM AIX, SCO UnixWare, DEC, Compaq, SGI, Linux), Macintosh System 8.x, 9.x, 10.x

Languages: Genuine Adobe® PostScript® 3™, PCL5e and PCL6 emulations with automatic sensing and switching

Paper Handling

Paper Input: 500 sheet tray: 60gsm bond to 200gsm cardstock, letter, statement, executive, A4, A5, B5-JIS, custom sizes and envelopes (monarch, com-10, C5/DL, custom)

150 sheet multipurpose bypass feeder: 60 to 135gsm bond, statement to ledger, A6 to A3, custom, up to 10 envelopes (monarch, com-10, C5/DL)

Automatic 2-sided printing†: 60 to 105gsm bond, statement to ledger, A5 to A3

500 sheet feeder† (A4/Letter-size tray): letter, statement, executive, A4, A5, B5-JIS, custom (A3/Ledger-size tray): ledger, legal, folio, letter, executive, statement, A3, A4, A5, B4, B5, custom

2,000 sheet feeder†: A4/Letter-size (can be used alone or with one additional 500-sheet feeder)

Paper Output: 500 sheets face down, 1,000 sheet Output Stacker†: maximum A4/Letter

WorkSet Special Features

Convenience Features: Edge-to-Edge Printing, Proof Print*, Secure Print*, Draft Mode, Collation, N-up Printing, Custom Paper Sizes, Booklet Printing, Watermarks, Fax-Friendly Black, Auto Size Sensing, Cover Sheets, Point and Print, Auto Tray Select, Separator Sheets, IPP

Productivity Features: Send Once/RIP Once/Print Many, Job Pipelining, Load While Run, Variable Fusing, Smart Jam Diagnostics, Automatic Tray Switching

Productivity tools for the IT manager: CentreWare Printer Management, MailInX email alert, Point and Print

Operating

Dimensions/Weight: 395 (H) x 490 (W) x 460 (D)mm/27kg

Environmental: Temperature: 5° to 35°C, Relative Humidity: 15% to 85% during operation, Noise Level: 35 dB(A) standby, 49.5 dB(A) running (ISO 7779, DIN EN 27779)

Electrical: 100 – 120V 50/60Hz or 220 – 240V 50/60Hz, Power Saver mode, Energy Star Compliant

Regulatory: FCC Part 15 Subpart B, UL listed to UL 1950, UL Certified to CSA – C22.2 No.950-M93, FDA 21 CFR Sub J, CE Mark applicable to directives 73/23/EEC and 89/336/EEC, TUV-GS Mark, IEC 950 Second Edition (A1-A4, EN 60950, EN 60825)

(*needs hard disk)

For more information, please contact:

Supplies

Consumables	
Print Cartridge (20K yield at 5%coverage)	113R00495
Maintenance Kit 220V (200K yield)	109R00522
Options†	
500 sheet Feeder (A3/Ledger-size tray)	097S02711
(A4/Letter-size tray)	097S02712
2,000 sheet Feeder (A4/Letter-size tray)	097S02714
Duplex Module	097S02713
1,000 sheet Output Stacker	097S02715
500 sheet Replacement Tray (A3/Ledger-size tray)	109R00523
(A4/Letter-size tray)	109R00524
Internal Hard Disk	097S02806
16MB DIMM	097S02356
32MB DIMM	097S02357
64MB DIMM	097S02358
8MB Flash DIMM	097S02360



THE DOCUMENT COMPANY
FUJI XEROX

FXAP 15400 D